



China 6204 Bearing Supplier



NSK NTN KOYO NACHI high precision manufacturer Price Single Row Deep Groove Ball Bearing 6903 6338 OPEN ZZ RS 2RS for auto parts

Bearing No. 6903

6903 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|--------------------------|
| Size | 17x30x7 mm |
| Bore Diameter | 17 mm |
| Outer Diameter | 30 mm |
| Width | 7 mm |
| d | 17 mm |
| D | 30 mm |
| B | 7 mm |
| C | 7 mm |
| r min. | 0.3 mm |
| da min. | 19 mm |
| Da max. | 28 mm |
| ra max. | 0.3 mm |
| Weight | 0.018 Kg |
| Basic dynamic load rating (C) | 4,6 kN |
| Basic static load rating (C0) | 2,55 kN |
| (Grease) Lubrication Speed | 24000 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NACHI |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.018 |
| EAN | 4991893812510 |
| Product Group | B00308 |
| Enclosure | Open |



China 6204 Bearing Supplier

| | |
|---------------------------------|---|
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 17MM Bore; 30MM Outside Diameter; 7MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.nachi.com |
| Weight / LBS | 0.04 |
| Outer Race Width | 0.276 Inch 7 Millimeter |
| Bore | 0.669 Inch 17 Millimeter |
| Outside Diameter | 1.181 Inch 30 Millimeter |
| Bore Type | Cylindrical Bore |
| Configuration | Single Row |
| Bore Size | 17 mm |
| Width | 7 mm |
| Fillet Radius/Chamfer | 0.3 mm |
| Dynamic Load Rating | 4,600 N |
| Static Load Rating | 2,550 N |
| Limiting Speed - Grease | 24,000 rpm |
| Limiting Speed - Oil | 29,000 rpm |
| | |



China 6204 Bearing Supplier

| | |
|------------------|-------------------|
| Factor fo | 14.7 |
| Radial Clearance | 0.003 to 0.018 mm |
| da (min) | 19 mm |
| Da (max) | 28 mm |
| ra (max) | 0.3 mm |